



F max. = maximum wall fixing force (kN)

NL	F max.
2450	6,9 kN
3000	8,3 kN

NL	2450						3000						
	NH	TH	H	DH	NW-AD	NW	NH	TH	H	DH	NW-AD	NW	
3400	3600	3800	4000	4200	4400	4600	3400	3600	3800	4000	4200	4400	4600
3875	4075	4275	4475	4675	4875	5075	3920	4120	4320	4520	4720	4920	5120
3452	3652	3852	4052	4252	4452	4652	3497	3697	3897	4097	4297	4497	4697

NL = Nominal length  
 NH = Nominal height Loadhouse  
 TH = Total height  
 H = Mounting (or fixation) height  
 DH = Loading dock height from ground  
 NW-AD = Width of Platform  
 NW = Total width of Loadhouse  
 FU = Free space under ceiling  
 IH = Installation height, Shelter from ground

Contact										
Pos	Quantity	NL	IH	NH	TH	H	DH	NW-AD	NW	<input type="checkbox"/> Yes <input type="checkbox"/> No Ceiling inside
Quote / Order Number		Project:			Notes:					
Date										
Drawn by										

<b>ASSA ABLOY</b> ASSA ABLOY Entrance Systems		Tolerance: EN ISO 13920-BF		Material: Norm: Treatment: Semifinished product:	Weight: N/A
Scale: Drawn: 21.01.2019 Checked: Blocked: Archived:	Date: 21.01.2019 Name: BARA01	Format: A2	Subject:	Architect/Building Preparation LH6180IL Mech. shelter without ext. roof - insulated wall	Drawing number: LH6180IL
Replaced by:				Revision: Sheet / of 02 / 1	Filename:
Index Modification Date Name					