



F max. = maximum wall fixing force (kN)

NL	F max.
2450	6,9 kN
3000	8,3 kN

NL	2450							3000						
	NH	3350	3550	3750	3950	4150	4350	4550	3350	3550	3750	3950	4150	4350
TH	3875	4075	4275	4475	4675	4875	5075	3920	4120	4320	4520	4720	4920	5120
H	3452	3652	3852	4052	4252	4452	4652	3497	3697	3897	4097	4297	4497	4697

NL = Nominal length
 NH = Nominal height Loadhouse
 TH = Total height
 H = Mounting (or fixation) height
 DH = Loading dock height from ground
 NW-AD = Width of Platform
 NW = Total width of Loadhouse
 FU = Free space under ceiling
 IH = Installation height, Shelter from ground

Contact										
Pos	Quantity	NL	IH	NH	TH	H	DH	NW-AD	NW	Ceiling inside
										<input type="checkbox"/> Yes <input type="checkbox"/> No
Quote / Order Number			Project:			Notes:				
Date										
Drawn by										

ASSA ABLOY ASSA ABLOY Entrance Systems		Tolerance: EN ISO 13920-BF		Material: Norm:	Weight: N/A
		Scale:	Format: A2	Treatment:	
		Date:	Name:	Semifinished product:	
		Drawn: 21.01.2019	BARA01	Subject: Architect/Building Preparation	
		Checked:		LH6180IL Mech. shelter with	
		Blocked:		extension roof - concrete wall	
		Archived:		Drawing number:	
		Replaced by:		LH6180IL	
		It is forbidden by law to copy, duplicate this document, to transmit it to any third party or to misuse it in any way. The drawing remains our property and is to be returned immediately after use.			Revision: 02
Index	Modification	Date	Name	Revision: 1	Sheet / of 1