



F max. = maximum wall fixing force (kN)

NL	F max.
2450	6,9 kN
3000	8,3 kN

NL	2450							3000						
	NH	TH	H	DH	NW-AD	NW	F max.	NH	TH	H	DH	NW-AD	NW	F max.
3350	3875	3452	3350	3350	3350	3350	6,9	3550	4075	3652	3550	3550	3550	6,9
3750	4275	3852	3750	3750	3750	3750	8,3	3950	4475	4052	3950	3950	3950	8,3
4150	4675	4452	4150	4150	4150	4150	8,3	4350	4875	4652	4350	4350	4350	8,3
4550	5075	5052	4550	4550	4550	4550	8,3	4750	5275	5052	4750	4750	4750	8,3
4950	5675	5652	4950	4950	4950	4950	8,3	5150	5875	5652	5150	5150	5150	8,3
5350	6275	6252	5350	5350	5350	5350	8,3	5550	6475	6252	5550	5550	5550	8,3

NL = Nominal length
 NH = Nominal height Loadhouse
 TH = Total height
 H = Mounting (or fixation) height
 DH = Loading dock height from ground
 NW-AD = Width of Platform
 NW = Total width of Loadhouse
 FU = Free space under ceiling
 IH = Installation height, Shelter from ground

Contact										
Pos	Quantity	NL	IH	NH	TH	H	DH	NW-AD	NW	Ceiling inside
										<input type="checkbox"/> Yes <input type="checkbox"/> No
Quote / Order Number			Project:			Notes:				
Date										
Drawn by										

ASSA ABLOY ASSA ABLOY Entrance Systems		Tolerance: EN ISO 13920-BF	Material: Norm:		Weight: N/A
Scale:		Format: A2	Treatment:		
Drawn:	Date:	Name:	Semifinished product:		
Checked:	21.01.2019	BARA01	Subject: Architect/Building Preparation		
Blocked:			LH6180IL Mech. shelter with		
Archived:			ext. roof - light concrete wall		
Replaced by:		Drawing number:		Revision: Sheet / of	
		LH6180IL		02 / 1	
Index	Modification	Date	Name	Filename:	