



F max. = maximum wall fixing force (kN)

NL	F max.
2450	6,9 kN
3000	8,3 kN

NL	2450				3000			
	FH	TH	H	DH	FH	TH	H	DH
3300	3600	3900	4100	3300	3600	3900	4100	
4275	4575	4875	5075	4320	4620	4920	5120	
3852	4152	4452	4652	3897	4197	4497	4697	

NL = Nominal length  
 FH = Free height  
 TH = Total height  
 H = Mounting (or fixation) height  
 DH = Loading dock height from ground  
 NW-AD = Width of Platform  
 NW = Total width of Loadhouse  
 FU = Free space under ceiling

Contact									
Pos	Quantity	NL	FH	TH	H	DH	NW-AD	NW	Ceiling inside
									<input type="checkbox"/> Yes <input type="checkbox"/> No
Quote / Order Number		Project:			Notes:				
Date									
Drawn by									

<b>ASSA ABLOY</b> ASSA ABLOY Entrance Systems		Tolerance: EN ISO 13920-BF		Material: Norm: Treatment: Semifinished product:	Weight: N/A
Scale:	Date: 21.01.2019	Name: BARA01	Format: A2	Subject: Architect/Building Preparation LH6180IL Inflatable shelter insulated wall	
Checked:	Blocked:	Archived:	Replaced by:	Drawing number: LH6180IL	Revision: Sheet/of 02 / 1
Index	Modification	Date	Name	Filename:	