



F max. = maximum wall fixing force (kN)

NL	F max.
2450	6,9 kN
3000	8,3 kN

NL	2450				3000				
	FH	3300	3600	3900	4100	3300	3600	3900	4100
TH	4275	4575	4875	5075	4320	4620	4920	5120	
H	3852	4152	4452	4652	3897	4197	4497	4697	

NL = Nominal length
 FH = Free height
 TH = Total height
 H = Mounting (or fixation) height
 DH = Loading dock height from ground
 NW-AD = Width of Platform
 NW = Total width of Loadhouse
 FU = Free space under ceiling

Contact										
Pos	Quantity	NL	FH	TH	H	DH	NW-AD	NW	Ceiling inside <input type="checkbox"/> Yes <input type="checkbox"/> No	
Quote / Order Number			Project:			Notes:				
Date										
Drawn by										

ASSA ABLOY ASSA ABLOY Entrance Systems		Tolerance: EN ISO 13920-BF		Material: Norm: Treatment: Semifinished product:	Weight: N/A
Scale:	Format: A2	Date: 21.01.2019	Name: BARA01	Subject: Architect/Building Preparation LH6180IL Inflatable shelter light concrete wall	
Drawn:	Checked:	Blocked:	Archived:	Replaced by:	
If it is forbidden by law to copy, duplicate this document, to transmit it to any third party or to misuse it in any way. The drawing remains our property and is to be returned immediately after use.				Drawing number: LH6180IL	Revision: Sheet/of 02 / 1
Index	Modification	Date	Name	Filename:	