



* By others, not included in the delivery.

- AD = Autodock
- NW = nominal width
- TH = total height
- DH = dock height
- H = fixing height
- NL = nominal length
- FP = fixing point
- n = fixing points qty.
- Fmax. = maximum wall fixing force

Fixing height H [mm]	insulated	unisolated	steelframe
680	TH - 240	TH - 180	TH - 60
681	TH - 255	TH - 195	TH - 75

Max. wall fixing force [kN]	NL 2000	NL 2450	NL 3000
680	6,3	6,3	7,5
681	4,9	4,9	5,9

	a	n
680	200	4
681	170	3

<small>It is forbidden by law to copy, duplicate this document, to transmit it to any third party or to misuse it in any way. The drawing remains our property and is to be returned immediately after use.</small>				General tolerance EN ISO 13920-BF				Material: Printed: 27.05.2014		Semifinished product: Weight:		Version: 2	
Drawn 10.10.2012 bra		Date 10.10.2012		Name bra		Scale: 1 : 20		Subject: LH6080L / LH6081L Insulated wall Installation		Drawing Number: 5144.0280		Sheet: 1	
Released 27.05.2014 Seubas		Blocked		Archived		Drawing Number: 5144.0280		Replaced by:		Format: A2		1 Sheets	
01 mod-no 12-14 14.05.2014 bra		Index Modification Date Name		ASSA ABLOY ASSA ABLOY Entrance Systems		Replaced by:		11		10		12	