



treaded bolt with
nut and washer

* By others, not included in the delivery.

- AD = Autodock
- NW = nominal width
- TH = total height
- DH = dock height
- H = fixing height
- NL = nominal length
- FP = fixing point
- n = fixing points qty.
- Fmax. = maximum wall fixing force

Fixing height H [mm]	insulated	unisolated	steelframe
680	TH - 240	TH - 180	TH - 60
681	TH - 255	TH - 195	TH - 75

Max. wall fixing force [kN]	NL 2000	NL 2450	NL 3000
680	6,3	6,3	7,5
681	4,9	4,9	5,9

	a	n
680	200	4
681	170	3

It is forbidden by law to copy, duplicate this document, to transmit it to any third party or to misuse it in any way. The drawing remains our property and is to be returned immediately after use.

General tolerance EN ISO 13920-BF	Date	Name	Material:	Semifinished product:	Version: 2
	10.10.2012	bra	Printed: 27.05.2014		
	Released 27.05.2014	Seubas	Scale: 1 : 20	Weight:	
	Blocked		Subject:	LH6080L / LH6081L Light Concrete Installation	
	Archived		Drawing Number:	5144.0279	
01 mod-no 12-14	14.05.2014	bra			Sheet: 1
Index	Modification	Date	Name	Replaced by:	1 Sheets
					Format: A2